



**ECO MIXER**



**SHUTTER MIXER**



**COMPACT SHUTTER**



**COMPACT SHUTTER**

## Gyroscopic Mixer

Details at glance :

- Auto clamping
- 3 selectable mixing speed
- Sliding out shelf
- Silent operation < than 70 db
- Max. Loading 40 KGS , 30 KGS for lab version
- Diagnostic on board
- Electronic mixing timer
- Sealed cabinet for safe washing
- Discharge tap
- 2 large back wheels for easy positioning
- Optional: check control mixing history
- User manual included



**40KGS Loading, Automatic**



Your tinting expert

# Gyroscopic Mixer

Patented and CE



Coloriance Gyroscopic mixers are a synonym of quality and durability at competitive prices. Capable of handling heavy loads of up to 40kgs to small laboratory test cans. The use of this mixing unit is virtually infinite. 3 speed selection guarantees an optional mixing time for all can sizes. Bottom plate slides out making it best to load all cans. Multiple cans can be loaded on the bottom plate.



- Color scheme may be adapted to customer requirement (standard is grey and blue).

## TECHNICAL PARAMETERS

Model	Eco mixer	Shutter mixer	Compact shutter mixer
Maximum Loading	40kgs	40kgs	40kgs
Maximum Can Size	39cm in Height	39cm in Height	38cm in Height
Minimum Can Size	8cm in Height	8cm in Height	11cm in Height
Round Can	37cm Diameter	37cm Diameter	32cm Diameter
Square Can	24.5cm Side	24.5 cm Side	
Can Type	Round / Square / Oval	Round / Square / Oval	Round
Multiple 1 Liter Can	Adaptor Up to 4 Cans	Adaptor Up to 4 Cans	
Auto Clamping	Cans are Clamped Automatically	Cans are Clamped Automatically	Cans are Clamped Automatically
Timer Electronic	From 1 to 9 Minutes	From 1 to 9 Minutes	From 1 to 9 Minutes
Internal Cabinet	With 1 See Through Swing Door	With 2 See Through Windows	With 1 See Through Windows
3 Speeds	90 – 140 – 200 RPM	90 – 140 – 200 RPM	90 – 140 – 200 RPM
Door	Swing Door	Shutter Door	Shutter Door
Loading Shelf	Sliding Out/Bottom Plate	Sliding Out/Bottom Plate	Sliding Out/Bottom Plate
Auto Indication	Electronic on Board (automatic speed detector optional)	Electronic on Board (automatic speed detector optional)	Electronic on Board (automatic speed detector optional)
Cleaning	Discharge TAP	Discharge TAP	Discharge TAP
Wheels	2 Wheels plus Fixed Feet	2 Wheels plus Fixed Feet	2 Wheels plus Fixed Feet
Sensors	On Door	On Door	On Door
Safety Sensor	Emergency Switch	Emergency Switch	Emergency Switch
Voltage	110–230 Volts 50/60Hz	110–230 Volts 50/60Hz	110–230 Volts 50/60Hz
MIXER Dimension	W76 × D95 × H105cm	W76 × D95 × H105cm	W67 × D75 × H100cm
Net Weight	167kgs	167kgs	135kgs
Motor Power	0.55 kw	0.55kw	0.55kw

Specification subject to changes without notice

## 40KGS Loading, Automatic