



SOLO



SOLO LARGE

## SoloPrima

- Class 4 tinting machine
- Simultaneous ~10 colorants
- 3 way solenoid valves
- Top canister colorant recirculation
- Individual canister stirring and individual safety fuse
- Keyboard, mouse, computer, LCD, and printer  
Housed on machine top
- Software link with Datacolor, Largo, and other  
end user own software
- Minimum dosing 0.078 ml. ( $1/384 \pm 2\%$ )
- LCD display to show functions at front
- USB-port connection
- Manual can shelf
- End user manual included



Simultaneous dispenser with colorant recirculation



Your tinting expert

# Soloprima *Patented and CE*

Class 4 tinting machine



**COLORIANCE**  
INTEGRATED COLOR SYSTEMS

Available from 12 to 24 circuits, offers simultaneous dosing of up to 10 colorants and real recirculation into the canister from the TOP. Our International Patented technology assures users of high productivity and reliability: not canister rotation or piston rotation, but a new concept (international patented) mode. Our Patented piston technology makes SoloPrima the most compact size in the market. New concept of canisters "holder bay" allows user's request of larger-sized canister (3~4 L) for frequently-used colorants and easier cleaning and maintenance. As always we offer an external dosing head that makes easier loading any pail or link SoloPrima to a roll conveyor. Autocap, wheels and many other optional fits are available.

## Note:

A Class 4 tinting machine is defined as tinting machine with simultaneous formula dosing (not just one colorant at the time) and recirculation of colorants at canister top. SoloPrima, performance of high budget machine at a sequential machine prices with the smallest footprint today in the market – only ~58cm in width. It fits everywhere.

## SPECIFICATIONS

Model	OPT	UM	SoloPrima
No. of circuits			12-24
Max. dosing circuit			~10 colorants at the same time
Colorants recirculation always			At canister top
Flow rate single circuit		ml/minute	Up~210
Flow rate per minute(5 Circuits)		L/minute	~0.81-1.2
Minimum dosing		ml	0.078ml-2% error
Pistons with triple teflon seals		ml	70Net-110-130Gross
3-way solenoid valves			YES
Auto cap	■		YES
Atomizer	■		YES
Movable shelf			YES
Auto shelf	■		YES
Canisters		L	2.2-4.4
Can and cap sensor			YES
Internal heating	■		YES
Motor power		Kw	0.55
Net weight		Kgs	180
Voltage		Volts	110/130/220/230
Frequency		Hz	50/60
SOLO dimension		cm	W58xD122xH136
SOLO large dimension		cm	W60xD128xH136
Software			Included
Software user interface/Spectra			WIN8/WIN10 – Any with Driver
Statistical software			YES
Calibration/Technical/Diagnostic		On Board	YES



Class legend	Definition
1	Manual dispenser
2	Sequential dosing no top canister colorants recirculation
3	Simultaneous dosing no top canister colorants recirculation
4	Simultaneous dosing and top canister colorants recirculation
5	Simultaneous dosing and top canister colorants recirculation. External tanks
6	Simultaneous dosing and top canister colorants recirculation. TDF

Specification subject to changes without notice

## Simultaneous dispenser with colorant recirculation